ADHESIVE FINDER

Find your perfect adhesive quickly! Choose the materials and features you require hereand find the stuff here	Wood to wood indoors	Wood to wood water resistant	Marine grade	Laminates to wood	Canvas to wood [edge of flats]	Canvas to plywood larger areas	Canvas to walls - removable	Muslin to polystyrene scrimming	Polystyrene sheet to poly.	Polystyrene to poly. gap filling	Flexible foams / PVC / inflatables	Wood to steel	Perspex to perspex	Glass, ceramics, stone	Costumes & Embellishments	Dance floor to plywood	Aluminium to aluminium or wood	Steel to steel	Structural adhesive	Poster to wall	Balsa to balsa or modelfoam	Wallpaper to wall	Wallpaper - frequent removal	Small jobs multi use	Fire retardant grade	Mastic type needing gun	Spray applied	Super fast	
General Purpose Adhesive				~					~			Ø				V									~				
Polystyrene Contact Adhesive				~			,		~			Ø				Ø													L.
Evo-stik 528 and 528 TX	~			~	~	~																							L
Evo-stik Impact	~			~								~		~							~			~					
Bostik 3206	~		~	~	~	~					~	~					~	•											Ļ
Treadfast 108																~													
Flints Cyclorama Glue						~	~	~	~							~				~									
FlintsBond	Ø					~		~												~									
Sheppy M289	~				7	~		Ø	Ø												Ø								
Clam 2					~	Ø		Ø	Ø											Ø									ł
Evobond	V					~		~	~											~	~								ŀ
Rosco Flexbond						~		r	~		~				Ø					~		~							-
Flintsdex / Copydex					~	~		~	~		~				Ø					~									ŀ
Great Stuff Pro Expand. Foam [pg 114]										~		~		~											~		~		ŀ
Granular Size	Ø				~	Ø		Ø																					
Pearl Glue	~				~	Ø		Ø																					-
Rabbit Skin Glue					~	Ø		Ø																					
Scotch Glue	~				Ø																								Ļ
Evo-stik Resin W	~	~		~																	~								
Flints PVA Wood Glue	~			~																	~								Ļ
Polyten	~	~		•																	~							~	
Polyproof	~	V	V	~					~										~										
Collano Semparoc	~	~	~											~					•										
Ampro Epoxy	~	~	V									~		~			~	~	~					~					
Araldite 2015 / Araldite Standard	~	~										~		~			~	~	~							~			Ļ
Hot Melt Glue Sticks	~											Ø		~			~	Ø			~			~		~		~	ion
Tuskbond XPRO	~	~		~								~													~		~	~	nlicat
3M Spraymount																				~							~	~	us an
3M Displaymount									Ø											~	~						~	~	for H
Ambersil NC500						Ø					~	~								~	~			~			~	~	anded
ldenden Multi Purpose						Ø					~	Ø								~	~			~			~	~) mmo
UHU Power Spray																				~							~	~	ot rec
Polycell Wallpaper Adhesive																						~							but n
Peel [plus above]																							~						alde
Stixall, Stixall Black	~	~										~	~	~			~	~			~			~		~			\mathcal{C} = usable, but not recommended for this application.
Gripfill	~	~		~								~		~			~	۲			~			~		~			R
Pinkgrip	~	~		~								~	~	~			~	۲			~			~		~		~	
Sabatack	~	~	~									~	~	~			~	~								~			ation
Tremsil 600														Ø	~											~			applic
Zap-a-Gap and Super Glues	~										~	~	~	~			~	V			~			~				~	this a
JB Weld	~											~		~			~	r						~					nd for
Bostik All Purpose / UHU	~			~							~	~	~	~			~	r			~			~					mmer
Gorilla Glue	~	~	~									~		~			~	r						~					= recommend for this application
E 6000+								~					~	~	~					~	~	~		~			•		7

T: 020 7703 9786

125

ADHESIVES

CONTACT ADHESIVES

Contact Adhesives

When using contact adhesives please follow the health and safety instructions carefully. Pay particular attention to ensure that there are no naked flames and, as the fumes are heavy, beware of low level pilot lights. When using these glues on polystyrene ensure that the glue has completely dried before joining sheets as trapped solvent can cause damage even with recommended adhesives. See also Resin 999 on page 120.

 \checkmark = suitable on polystyrene \checkmark = NOT suitable on polystyrene



General Purpose Adhesive [polystyrene ✓] This is a very popular brushgrade general purpose contact adhesive. It will work on painted or unpainted steel. This adhesive has a strong wet tack for fibrous materials and excellent adhesion. When working with polystyrene only use it as a contact adhesive allowing each side to thoroughly dry before bringing the surfaces together. It rapidly dries in 15 minutes and

when dry conforms with BS 476 Part 6 and Part 7 Class 1 fire rating suitable for stage use behind the iron. Toluene-free. UN 1133. Covers 4 m^2 per litre.

			Tradeline	
General Purpose Adhesive	code	5 L	5+	
	ADH1088	£46.89	£40.15	



Polystyrene Contact Adhesive

[polystyrene ✓] Previously called Tretobond 375, this is a synthetic rubber-resin contact adhesive based in a blend of solvents. Used for the bonding of expanded polystyrene to itself, and to other smooth surfaces. Both surfaces require a thin uniform coat; the adhesive spreads easily. The surfaces must be completely dry [otherwise the trapped solvents can have a deleterious effect on

polystyrene] before they are brought together preferably under pressure. Health and Safety information should be strictly followed. Do not mix the cleaner into the glue.

Polystyrene Contact Adhesive	code	5 L	5+
	ADH063	£62.93	£59.50
AW 421 Industrial Cleaner	ADH068	£30.96	-



Evo-stik 528 [polystyrene X] A synthetic rubber resin contact adhesive based in a blend of solvents. The most popular general purpose contact adhesive particularly suitable for bonding decorative laminate sheets and rigid plastic sheets of PVC or ABS. New faster drying formula. Adhesive: UN 1133. Cleaner: UN 1993.

size	code	list	price
1L	ADH081	£41.87	£21.32
5 L	ADH082	£123.85	£92.10
5 L	ADH083		£63.50
	1 L 5 L	1 L ADH081 5 L ADH082	1 L ADH081 £41.87 5 L ADH082 £123.85



Evo-stik TX 528 [polystyrene X] Just like the Evo-stick 528, a synthetic rubber resin contact adhesive but with a thixotropic agent which makes it much easier to apply. This jelly-like adhesive spreads like soft butter rather than hot gruyère. Ideal for use on large and vertical surfaces as well as intricate work. It is easier to control and less likely to stray onto clean areas. Particularly suitable for bonding decorative laminate sheets and rigid

plastic sheets of PVC or ABS. Adhesive: UN 1133. Cleaner: UN 1993.

Evo-stik TX 528	size	code	list	price
Evo-stik TX 528	1L	ADH079	£44.63	£22.89
Evo-stik TX 528	5 L	ADH0792	£129.50	£97.11
Evo-stik 191 Cleaner	5 L	ADH083		£63.50



Evo-stik Impact [polystyrene X] Similar to the 528, this contact adhesive bonds decorative laminates, wood, chipboard, hardboard, rigid PVC, ABS plastics, leather, cork, stone, china and earthenware. Sold in small sizes for convenient storage in the touring prop skip.

Transfallers

Evo-stik Impact	size	code	price	12+
Small tube	30 g	ADH0862	£4.48	-
Large tube	65 g	ADH0861	£7.75	-
Small pot	250 ml	ADH086	£9.50	-
Large pot	500 ml	ADH087	£18.04	£15.55
Large pot	500 ml	ADH087	£18.04	£15.55

WATER-BASED CONTACT ADHESIVES



Treadfast SF 108 A pressure sensitive adhesive for vinyl floor and wall coverings. It is solvent-free nonflammable and has low toxicity. Treadfast 108 will give a strong permanent bond. Use a notched trowel to apply and immediately roll with a paint roller wetted with the adhesive. Allow to dry [goes clear] then position and roll with 68 kg roller. Covers 6 – 8 m² per litre.

Treadfast SF 108 size	code	Tradeline
5 L	ADH1085	£56.54
15 L	ADH10815	£152.30
Notched Trowel	ADHTAS007	£15.80

2: ADHESIVES

See also Bostik Inflatable Adhesive on page 130.

CLOTH ADHESIVES



Copydex Adhesive Natural rubber latex solvent-free non-flammable adhesive used widely for bonding canvas, serge, velour as well as paper, card, cork, plastic, etc... When using with serge or velour the adhesive will show through if too much pressure is applied. It can be used as a contact or wet bond glue. size code price 125 ml ADH092 £6.02

£16.93

ADH097

What happened to Copydex!

500 ml

What a strange thing! We used to sell pallet loads of Copydex in 5 L pots but the manufacturers decided, in their infinite wisdom, to only do silly little pots. We pleaded on your behalf but to no avail. We don't particularly want to have adhesives especially made for us but we had our hand forced. So if you want large quantities of Copydex why not try Flints...dex 4.



Flints...dex A quick grab latex adhesive for use on paper, card, wood, plastic, metal, cork, fabric, carpet, leather, canvas and many more materials. If making cut cloths be sure to dust any excess glue with French Chalk [page 25] before rolling up to prevent accidental dry contact gluing.

- ✓ Safe and easy to use ✓ Solvent-free
- Economically priced
 Water-based

✓ Free flowing – apply by brush or spreader Can be used to coat the back of floor cloths for a non-slip finish

Flintsdex	size	code	price	10+
	5 L	ADH089	£59.00	£50.75



Clam 2 Brummer Latex Adhesive A rubber latex solvent-free non-flammable

adhesive which provides an exceptionally strong bond with a good open time for working on large areas. Thixotropic, it can be applied by brush or roller and is generally used for fixing canvas to open framed flats – see below ↓.

Clam 2 can also be used for bonding leather, cork, card, etc.

✓ Tenacious strength

T: 020 7703 9786

Clam 2	size	code	price
	1L	ADH094N	£15.32
	5 L	ADH095N	£59.98

Canvassing open frame flats with Clam 2

Firstly, staple your scenic canvas 6 mm in from the inside edge of the frame along the long edge, flap back the canvas revealing the frame, brush on the Clam, fold back the canvas and rub with a piece of timber with the arris removed to force the glue into the material. Once the long edge has set [just a few minutes] staple the canvas around the rest of the frame [ensuring it is kept square] and repeat using the same technique. The Clam 2 is strong enough to stop the canvas puckering up behind the staples. Once the whole flat is glued down, take a "Stanley" knife with a sharp blade and trim off the excess canvas about 4 mm in from the flat's outer edge using your thumb as a guide. Trim a little bit off the corners at 45° and that's it. Allow overnight before priming.



Flints Cyclorama Glue

This best-selling environmentally friendly glue is water-based and safe to use. We highly recommend it for sticking large canvas murals and cycloramas but it has many other uses including bonding vinyl dance floor to plywood or hardboard. Many of our clients use it to consolidate texturing compounds such as rubber crumbs. It makes a great polystyrene adhesive too! It can be used as a dry bond, wet bond or contact adhesive.

Its unique advantages when used as a **dry bond** are:

✓ **No bleed through** The glue will not damage the artwork. As the glue is only applied to the wall and the cloth is positioned when the glue is dry it cannot bleed through.

Repositionable If you get a wrinkle in your cloth or it goes out of alignment just gently peel back and try again.

✓ Removable It is not permanent. You can actually remove the artwork from the wall when you have finished and no glue sticks to the canvas. Just roll the canvas up and transport to the next venue. It saves having to slit cloths down scenery joins after the first venue of a tour and allows expensive scenic artwork to travel separately from its heavy backings.

✓ Paint off site Murals can be painted in the artist's studio rather than having to close down public areas of museums etc. while the painting is taking place.

✓ Water-based It is water-based and is safe to use in areas where other contact adhesives could not be risked. The virtual lack of odour makes it a good choice when venues need to be re-opened quickly, reducing down time.

✓ Multi-Purpose The glue can also be used as a wet lay or double bond for more permanent applications. It is suitable for bonding vinyl and rubber as well as natural cloths.

✓ Easy and clean to use The adhesive comes with simple instructions and your tools just clean in water.

Application is best using a notched trowel with 2 mm notches every 5 mm [see page 131] and then rolling with a pre-wetted short pile roller to provide a completely smooth surface.

Covers approximately 4.5 - 5 m² per litre. Also in 15 L pails.

The Three Methods

Dry Bond Apply the adhesive to the wall and allow to dry. Gently position the cloth on the wall, adjust as necessary, then press down firmly. The cloth can be removed at a later date by peeling off.

The Double Bond Flints Cyclorama Adhesive performs well as a waterbased contact adhesive. Apply adhesive to both the wall and the cloth. Allow to dry. Press the cloth onto the wall for a permanent bond. This method will provide a strong bond for many surfaces including dance floors.

Wet Bond Use as a conventional glue. Apply the cloth to the wet adhesive and allow to dry for a permanent bond. Use it to consolidate texturing compounds such as foam crumbs.

Flints Cyclorama Glue	size	code	price	Tradeline
	5 L	ADH130	£58.25	-
	15 L	ADH131		£156.89
Notched Trowel		ADHTAS007	£15.80	



FlintsBond

FlintsBond A waterborne PVA emulsion which is easy to spread. Suitable for use as a primer or for gluing cloths such as light canvas, calico or muslin to flats or for scrimming polystyrene. It can also be used as a concrete dust sealer by diluting 50% with water and applying with airless spray, brush or roller. It dries clear. Covers 3 - 5 m² per litre.

size	code	price
5 kg	ADH141N	£24.00
25 kg	ADH142N	£98.00



Sheppy PVA M289 A replacement for the popular M155 - this is a medium viscosity compounded emulsion glue. It has good running characteristics and dries to a strong flexible film. Excellent for gluing large areas of canvas and very popular with the big

workshops. Also suitable for conservation work as the dried adhesive film will de-laminate in the presence of water.

Easy spreading for large areas

Sheppy PVA	size	code	price	10+
	12.5 kg	ADHM289	£89.75	£80.65



Evo-bond A universal adhesive, sealer and primer. Improves adhesion when used as a primer and will effectively bond many light sheet materials and cloths. Excellent value.

ļ	Evo-bond	code	price
/	5 L	ADH025	£34.45



Rosco Flexbond Adhesive Clear flexible scenic glue which bonds many porous and non-porous scenic materials. Dries to a clear hard but pliable coating that does not remain "tacky" as other flexible coatings do. The adhesive bond does not crack and break when flexed. Recommended for bonding textures such as micafil and rubber granules. This adhesive also works well on polystyrene. Flexbond is water-based and safe to use.

Rosco Flexbond

Canvassing with hot size

size

3.79 L

18.95 L

✓ Clear and very flexible

code

R0S60753

R0S60750019

Size is best used on open frame flats as it is too difficult to maintain a hot fluid glue on ply clad flats [use Sheppy M155 for ply clad flats]. For open frame flats, staple your scenic canvas 6 mm in from the <u>inside</u> edge of the frame along the long edge, flap back the canvas revealing the frame, brush on the hot size to the timber with a glue brush. While the glue is still warm, fold the canvas down and swab through with a warm damp cloth until a soap appears on the surface of the canvas. Ideally, this is done with two people, one gluing and the other swabbing. Keeps you lovely and warm, although you won't smell great. Repeat on the other three sides once the long edge has set up. Trim 4 mm in with a sharp "Stanley" knife.



Granular Size The most popular traditional glue for sticking canvas to timber flats and also used in the preparation of traditional primers and scenic paints [page 24]. To prepare size as a glue, mix 1 part of size with 1.5 parts of water whilst agitating. Leave to

soak for one hour. Then dissolve by warming in a double bucket [water jacket] diluting further to a working consistency. Do not exceed 55°C.

Granular Size	code	1 kg	code	25 kg
	PAT852	£11.38	PAT852B	£226.65

For glue brushes see page 74.



Pearl Glue Like granular size but supplied in a pearl form. Traditionally used for sticking canvas to flat frames. Add 1 part of glue to 1.5 parts of water whilst agitating. Leave to soak for one hour and then dissolve by warming in a double bucket. It can be diluted further with water. Do not exceed 55°C. Use while warm.

Tradeline

Pearl Glue	size	code	price	25+
	1 kg	ADH096	£20.75	£18.68



Rabbit Skin Glue The preferred glue of non-vegetarian fine artists for sizing canvas and making gesso.

Rabbit Skin Glue	code	price
500 g	ADH098500	£21.71

WOODWORKING ADHESIVES



Scotch Glue A high quality jelly bone glue, manufactured from selected raw materials. It has a breaking strain far in excess of BS 745. It is recommended for antique restoration, chair frames, veneering, and any trade where a first class, long-lasting joint is necessary. Preservatives in this formulation keep the glue free from mould and bacteria for a long time

in the glue pot. Its slower setting characteristics enable the glue to penetrate hard woods and provides a longer open time for intricate assembly work and veneering operations. To use: Warm gently until it reaches the consistency of paint, never so hot that it shows steam.

Scotch Glue	size	code	price
	1 kg	ADH0071	£12.56



Evo-stik Resin W A one-part synthetic resin emulsion adhesive for bonding hard and soft woods. Widely used for framework assembly, bonds wood veneers and laminated plastics to wood and chipboard. Complies with BS 4071:1966.

Evo-stik Resin W	size	code	price
	250 ml	ADH0841	£5.82
	500 ml	ADH0842	£9.21
	1L	ADH084	£17.76
	5 L	ADH085	£73.61

price

£74.00

£339.25





Flints PVA Wood Glue 5 kg own-label replacement for Evo-Stik's popular Resin 168. We hope this will become the go-to PVA for scenic workshops for many years. It is a quality, costeffective PVA for the frequent user with strong adhesion just 20 minutes after application. Edd Smith, the Workshop Manager at Scottish Opera, fed back "we will be moving to the new Flints product

straight away". It is suitable for bonding wood to wood and Formica to wood. It is not designed to be used in a wet environment. We supply it in 5 L containers and also in handy 25 L plastic drums with a tap for easy dispensing. Covers approximately 7.5 m² per litre.

Flints PVA Wood Glue size	code	price
5 kg	ADH305	£37.00
25 kg	ADH325K	£145.00



Polyproof A completely water resistant resorcinol glue suitable for boatbuilding with continuous immersion in water [even boiling water!]. Used for the construction of laminated roof beams and bridge arches. Glues polystyrene, Formica and difficult timbers like teak. Superior to epoxy in terms of proven longevity, ideal for mast making. Consists of a liquid resin with a powder hardener.

SPECIFICATION: Flame resistant to Class O. Approved by NTI Norway, Otto Graf Institut [FMPA] Germany, SKH/KOMO [DHBC No 32389] Holland for the production of load bearing timbers. Fulfils the requirements of EN 301 [for glue types 1 and 11, service classes 1,2,3], EN391, EN392 and DIN 68141.

S	ize	code	price
6	570 g	ADHAPP670	£34.47



Polyproof

Polyten Extra water resistant wood adhesive, with a new ten minute fast grab formulation that can be handled within 30 minutes. Suitable for all woods, interior and exterior use. It is not suitable for continuous immersion in water. It dries clear and can be applied by brush, roller or straight from the bottle.

Polyten	size	code	price
	1L	ADHAPT1	£8.48
	5 L	ADHAPT5	£34.39



Sempar

Collano Semparoc One-component PUR adhesives with high bond strengths and a choice of open time. Suitable for waterproof [EN 12765] and weather resistant bonding of all timber materials, stone, cement-based boards, cork etc. They are suitable for assembly work and for use with hardwoods, softwoods and non-flammable building boards. This glue effectively replaces Balcoton and has the advantage that it tends to foam up less. **Semparoc 60** gives approximately 1 hour working time.

SPECIFICATION: Viscosity at 20°C: » 8,500 mPa [4/20], density 1.25 g/ml,. Solids content: 100%. Waterproof resistance: C4 in accordance with EN 12765. Flame resistance: EN 13501 to F120 [with corresponding materials and construction]. Heat resistance: to +120°C. Shelf life: 9 months. Spread rate: 100 - 300 g/m².

°0C	working time	code	800 g
Semparoc 60	60 min	PATCS60	£27.45

STRUCTURAL ADHESIVES



Araldite 2015 Structural Adhesive With the legendary strength of epoxy. Excellent bonding of aluminium, mild steel, stainless steel, copper, zinc and galvanised steel. Good bonding of rubber, glass, ceramics; and moderate bonding of polycarbonate, PVC, ABS and polystyrene. Perfect for use with Aerolam lightweight honeycomb panels. Dispensed with handgun via a self-mixing nozzle.

Two-part Araldite Epoxy	size	code	price
	200 ml	ADH20151	£31.50
Skeleton Gun [shown]		ADHVBM200	£38.96

EPOXY



Ampro Multi-Purpose Epoxy

System This is a simple to use, allpurpose epoxy which can be used for:

```
    ✓ Gluing
    ✓ Laminating
    ✓ Filling
```

With its range of hardeners and easy 3:1 mix ratio by volume, Ampro provides a quick and convenient way of using one

epoxy system for a very wide range of tasks – a re-engineered version of the popular SP 106. Widely used in many woodworking applications from cabinet making, to wooden boat repair, to the manufacture of large wooden moulds. By using Glass Bubbles or Micro Fibres [page 121], an Ampro resin and hardener mix can be turned into a very effective filling compound or gap filling adhesive. We can supply larger sizes to order. For user instructions visit flints.co.uk/downloads.

Ampro Multi-Purpose Epoxy resin/hardene	r code	price
1.33 kg pack + fast hardener 1 kg / 333 g	ADHF530025	£43.15
1.33 kg pack + slow hardener 1 kg / 333 g	ADHF530027	£43.15
4.2 kg pack + fast hardener 3 kg / 1.2 kg	ADHF530026	£109.09
4.2 kg pack + slow hardener 3 kg / 1.2 kg	ADHF530028	£109.09
10 kg resin only	ADHF530080	£165.53
3 kg fast hardener [for 10kg]	ADHF530013	£115.90
3 kg slow hardener [for 10kg]	ADHF530017	£115.90



Ampro Handipack This convenient little pack is perfect for small props and general repairs. It consists of resin, hardener and dispensing pumps. simply pump 3 pumps of resin to 1 pump of hardener for the perfect ratio to mix. Complete with instructions, this high clarity, and low-temperature curing pack will prove invaluable in any props workshop.

Ampro Handipack

resin/hardener_code price 290 g / 85 g ADHF530071S £31.58

129

GLUE STICKS

2: ADHESIVES

R



flowers and delicate materials. SPECIFICATION: Ø: 12 mm. Length: 190 mm. Colour: None. Opacity: Transparent. Melt Temp: 200°C.

Rapid Brand Glue Sticks	size	code	list	price
	1 kg	ADH40302799	£28.75	£25.25



Low Temperature Glue Sticks Suitable for bonding materials that may be affected by high temperatures. SPECIFICATION: Ø:12

Tradeline

£56.77

mm. Length: 190 mm. Colour: None. Opacity: Transparent. Melt Temp: 130-150°C.

Rapid Low Temp Glue Sticks	size	code	list	price
	1 kg	ADH221	£33.90	£27.38



Black Glue Sticks Highquality coloured hot melt adhesive. For bonding a variety of materials.

SPECIFICATION: Ø: 12 mm. Length: 200 mm. Colour: Black. Opacity: Opaque. Melt Temp: 240°C

Black Glue Sticks	qty	code	price	qty	code	price
	8 sticks	ADHBGS8	£8.50	1 kg	ADHBGS1	£29.85

Other coloured and glittered glue sticks can also be ordered in [subject to minimum quantities]. Please call and ask for prices.



GLUE GUNS

Steinel 5000 Cordless Glue Gun This is a cordless glue gun for real versatility yet the cord can also be plugged directly to the gun for continuous output.

SPECIFICATION: Glue Output: 22 g per minute. Heat time: 3-5 mins. Weight: 330 g. Operating Temperature: 210 -220°C. Stick Ø: 11 mm. Power: Mid-Operation: 500 W; Standby: 20 W

coae	list	price
P0W332716	£76.45	£65.74

Steinel Glue Gun Spare Nozzle 2.8 mm

> price £6.60

code
P0W075965



Steinel 5000 Cordless Glue Gun

Steinel Nozzle 2.8 mm

Bosch PKP18E A good quality, very popular general purpose gun. Ideal for prop shops and display work. SPECIFICATION: Glue output: 20 g per minute. Heat time: 7 mins. Weight: 350 g. Operating

temperature: 200°C. Stick Ø: 11 mm. Power: Mid-Operation: 200 W; Standby: 16 W. **Bosch PKP18E** code price P0W090 £24.50



Rapid Cordless Glue Gun Glue Gun Spare Battery



Rapid Cordless Glue Gun BGX300 New heater,

bi-injected handle, innovative trigger system and Li-ion technology provide full flexibility, freedom and comfort to bond all kinds of material.

SPECIFICATION: Battery: Li-ion 7.2 V 2.6 Ah. Heating time: 4 min. Glue output: 350 g/h. Stick Ø 12 mm. Power: 30 W. Weight 900 g.

code	list	Tradeline
STPBGX300	£113.05	£81.85
STP40303077	£61.15	£52.68

Rapid Professional Glue Gun EG340 A high output glue gun that will reach working temperature very quickly and provides a choice of constant working temperatures. Features include an integrated thermostat, replaceable nozzle and long 2.5 m cord.

SPECIFICATION: Glue Output: 23.3 g per minute. Heat time: 2 mins. Weight: 0.93 kg. Adjustable temperature: 120°C- 220°C. Stick Ø: 12 mm. Exchangeable Nozzle Ø: 3 mm. Power: 220 W

Rapid Professional Glue Gun EG340	code	list	price
	POWEG340	£226.15	£155.70
Extended Nozzle for EG340	P0W5000200	£39.95	£38.77
Wide Spread Nozzle for EG340	P0W5000201	£39.95	£38.77

Sticky Fingers? Why not order a pack of **Biodegradable Wipes [page** 364]. They remove paints and ahesives from your hands and gently condition the skin.

ADHESIVES FOR INFLATABLES



Bostik 3206 A polyurethane-based contact adhesive specifically formulated for bonding both plasticised and unplasticised PVC to a wide range of substrates. Typically used to make inflatables. This adhesive has less initial grab than conventional contact adhesives and requires a little more pressure, however the ultimate bond is very powerful.

Bostik 3206	size	code	price
	1L	ADH3206	£42.19

Struggling to find what you need? Why not give us a call, or pop into our trade counter?

Our team are always happy to help you get exactly what you need. If we don't stock something the fits the bill, we will always do our best to source it for you.

WALLPAPER ADHESIVES



Polycell Max Strength Wallpaper Adhesive Each box will hang up to 20 rolls. My goodness what a long code!

Polycellcod	е	price
	ADHPLCMSWPA20R	£8.63



Peel A revolutionary product which allows wall coverings to be removed from a wall without soaking or scraping. Coat the walls with Peel before you hang your paper and when you redecorate the old paper pulls off in complete lengths. Ideal for TV, theatrical and display applications where frequent decoration is necessary. Also see also Peelable Paint [page 64] and Mask It [page 275]. size code price

ADH112

Peel

ADHESIVE TROWELS



5 L

Notched Adhesive Trowel For rapid and even application of most contact adhesives over large areas. The large trowel has B1 notching [2 mm deep x 2.4 mm wide, every 5 mm]. The small one is much finer with 1.5 mm deep notches about 1.66 mm apart.

£69.98

Adhesive Trowel	serrations	code	price
Large with handle	2 mm every 5 mm	ADHTAS007	£15.80
Spare blade for above	2 mm every 5 mm	ADHTAS007B1	£5.23
Small	2 every 1.66 mm	ADHT850	£5.29

SPRAY APPLIED ADHESIVES



TuskBond XPRO Rising prices are affecting us all and the same is true within the realm of contact adhesives. So we have made a decision to drop the popular TensorGrip L17 Adhesive and replace it with TuskBond XPRO. A brand new product, TuskBond XPRO uses the latest solvent technology to make an adhesive that rivals Tensorgrip in

terms of performance but is lower toxicity and non - chlorinated, a win -win. For use with Spray Gun and Hose. Also available in 500 ml aerosol

- ✓ Great for covering large areas.
- ✓Great for permanent bonds with high initial bond.
- ✓Fast Drying
- ✔Web Spray Pattern

Suitable for: ✔Wood ✔ Metals ✔ Rubber ✔ Fabric ✔ Cardboard ✔ Polythene ✔ Concrete ✔ Laminates ✔ Most Plastics.

✗ Not for use with Vinyls containing large amounts of plasticiser as it can migrate over time.

Specification Coverage: 100 m² per tank Meets specification of BS 476: Part 7: 1997 Class 1 Fire Rating SAFT Heat Tested 100°C

TuskBondXPRO	size	code	Tradeline
Adhesive	22 L	ADHTUSKT	£169.00
Gun		ADHTUSKG	£65.35
Hose	4 m	ADHTUSKH	£73.85

AEROSOL ADHESIVES



TuskBond XPRO Aerosol Aerosol version of the TuskBond Pro listed in the previous column. Replacement for the popular Tensorgrip L-17. More convenient size, all the same features.

TuskBond XPRO Aerosol

```
size code
500 ml ADHTUSKA
```



3M Spray Mount Provides an instant repositionable adhesive for most surfaces. The controlled spray pattern reduces adhesive mist. Ideally suited for mounting light materials where the fine texture of the adhesive is unlikely to cause disturbance to the face surface. For heavier materials try Display Mount. UN 1950

price

£17.35

price

£14.98

3M Spray Mount size code 400 ml ADH120

Now cheaper!

size

400 ml

*: *	
	3M
	Display Mount
	Drimanent A dhenire Mhoiko Permanenie Miniso Permanenie Asprozakskali kzeli
	ED.

1

3M Display Mount The ideal choice for mounting exhibition lettering in foam, card, plastic or fabric. Can be used on polystyrene if applied thinly to prevent any solvent entrapment. UN 1950.

code

ADH121

3M Display	Mount	•••



Ambersil NC500 Suitable for paper, rubber, plastics, fabrics, foam, wood, metals, hessian, cork, felt, upholstery, carpets and flooring. A slightly coarser spray pattern than the 3M sprays but great value for a large 500 ml can. UN 1950

Ambersil	NC500	





Bostik Sprayable Adhesive [polystyrene X] Replacement for the popular Idenden Spray Adhesive. We've tested it and can't tell the difference! A seriously economical spray adhesive that is perfect for bonding polyurethane foam, felt, cork and most plastics to wood and steel. There is a variable spray nozzle enabling large or small areas to be coated without overspray. Glue wastage is eliminated and it is a quick, clean and efficient

means of bonding. Contains no Methylene Chloride. UN 1950 Bostik Sprayable Adhesive code price

e Adhesive	code	price	12+
500 ml	ADH140N	£8.98	£7.82



UHU Power Spray A basic spray adhesive similar to Display Mount, with a very fine spray pattern, and we found there was no bleed through when testing on paper and card.

UHU Power Spray	code	price
200 ml	UHU362938	£8.95

For Expanded Foam Aerosols see page 114.

price

£6.85

Tradeline

12+

<u>Tradeline</u>

12+

£14.05

£16.50

MASTIC ADHESIVES

2: ADHESIVES



Sabatack 750 XL This is our replacement product for Sikaflex 291. It is an MS Polymer that adheres superbly to metals and plastics. Its principle use would be to make gap filling high tensile bonds of fittings to ships and trucks etc. It can be used anywhere where dissimilar materials need bonding, with the mastic also forming a waterproof seal all in one process. May be used for bonding teak decking down to substrates.

- ✓ Fully UV stable ✓ Can be easily overpainted
- ✓ Contains no solvents or isocyanates

SPECIFICATION: Hardness: shore A 55. Skin time: 15 minutes. Open time: 30 minutes. Viscosity: medium. Green strength: low. Cure rate: 3mm/24 hr. Tensile strength: 2.6N/mm². Shear strength: 1.7N/mm². Elongation at break: 330%. Temperature resistance: -40°C to +120°C. Shelf life: 18 months



Stixall, based upon new hybrid PMS polymer technology, is the ultimate combined building adhesive and sealant, with the power to bond and seal virtually everything to anything. Stixall offers almost limitless benefits as a permanently flexible adhesive and sealant, removing the application barriers associated with conventional products.

- ✓ Stops mould growth
- ✓ Clear version is crystal clear
- Solvent-free, no odour
- Overpaintable
- High bond strength
- ✓ Exterior or interior use
- ✓ Resistant to chemicals ✓ Totally waterproof
- ✓ Resistant to temperature extremes
- ✓ Incredible initial grab, no slip, gap filling
- Can be applied to wet surfaces

✓ Sticks glass, granite, brick, ceramics, fibreglass, mirrors, all hard plastics, timber, roof tiles, marble, stone, all metals and much more!

40-Year Lifetime Guarantee!



Gripfill [polystyrene X] A market leading high strength gap filling mastic adhesive suitable for bonding wood, laminated plastic, metal, stone, ceramics, GRP and aluminium. One cartridge will provide a 6 mm bead approximately 10.25 m long.

Gripfill	cartridge	code	price	Tradeline 12+
	350 ml	ADH077G	£3.25	£2.90





Pinkgrip Richard Black just insisted that we stock this product which has an instant strong grip with no drooping. Battens can just be stuck to a wall where they will remain without additional fixings even while the glue sets. He raves about its qualities as if he owns shares. Richard claims to have built entire sets just using Pinkgrip, let's just hope he doesn't get into aeronautics. The Solvent-free version is brilliant for using with acrylic mirror.

Pinkgrip	cartridge	code	list	price	Tradeline 12+
Standard	350 ml	ADHPG	£3.49	£3.15	£2.95
Solvent-Free	350 ml	ADHPGSF	£4.92	£4.45	£4.25

MASTIC SEALANTS



FAGOO (Tremsil) A medium modulus neutral silicone sealant. Good for general purpose sealing and caulking. It is ideal for bedding in glass. Conforms to BS 5889 [1989] Type A. These silicone sealants do not make high tensile bonds so products bedded with them can normally be removed without too much disruption to the substrate.

FA600 (Tremsil)	cartridge	code	price	
Black	310 ml	ADH600	£9.98	£9.48
White	310 ml	ADH600W	£9.98	£9.48
Translucent	310 ml	ADH600T	£9.98	£9.48

MASTIC GUNS

Flints only stocks top quality Cox mastic guns which will not crumple up when you are halfway through a Sunday fit-up. UK manufacture.

Easiflow HD



tradesman whose work includes the semifrequent application of sealants. It has been produced continuously since 1971 and differs from imitators by having up to ten times the working life of some models. It has a 7:1 ratio tric

working life of some models. It has a 7:1 ratio trigger and a patented pressure release device which virtually eliminates sealant "flow-on". The drive rod is bent to provide a handy hook.

Easitiow HD Sealant Gun	code	price
400 mm [to suit up to 400 ml tubes]	ADH303	£7.76

Powerflow Cartridge

An advanced applicator designed for those who use sealants on a daily basis. The die cast trigger is ergonomically contoured for all hand sizes providing comfortable operation over long periods. The 12:1 ratio permits very smooth se

periods. The 12:1 ratio permits very smooth sealant flow for a high quality finish. A good choice for deck caulking.

Powerflow Cartridge	code	price
400 mm [to suit up to 400ml tubes]	ADH304	£21.37

For Twin Cartridge Guns see page 129.

132

PROP SKIP ADHESIVES



UHU® and UHU® Gel Strong crystal clear adhesives suitable for virtually everything except expanded polystyrene. The UHU gel is a non-drip version which many find cleaner and easier to use.

UHU®		size	code	price
	UHU® All purpose	35 ml	UHU042862	£2.76
	UHU® Extra Gel	31 ml	UHU043437	£2.76



Araldite® Standard Supplied in a syringe, this is a strong solvent-free adhesive suitable for all materials and ideal for durable bonding and repairs. Perfect for complicated jobs which require adjustment thanks to a long working time. It will bond metals, wood, pottery, glass, and most hard plastics.

Araldite® Rapid A rapid fixing two-part epoxy adhesive. Supplied in an easy to use syringe dispenser.

Araldite®	size	code	price	Tradeline 12+
Standard Syringe	24 ml	ADH154	£6.37	£5.75
Rapid Syringe	24 ml	ADH153	£6.37	£5.75



Zap-a-Gap Fills Gaps, allows 7-10 seconds for positioning and cures in 20 seconds. Bonds most materials including metal, wood, rubber, pottery, and most plastics. The cure can be speeded up by using the aerosol Kicker accelerator.

Zap-a-Gap	size	code	price
Adhesive	1 oz	ADHPT02	£7.08
Adhesive	4 oz	ADHPT05	£24.13
Accelerator	2 oz	ADHPT15	£6.55



Loctite Super Glue A high performance instant cyanoacrylate glue. Not suitable for glass, polypropylene, polyethylene, and other waxy surfaces.

uper Glue	size	code	price
	5 g	ADH100	£4.36



JB Weld One of the world's strongest adhesives! You can drill it, grind it and machine it! Always handy for those unexpected breakages. Bonds steel, aluminium, wood, copper, ceramics etc.

J	ł	3	1	V	١	6	2		I	(
		• •						1	÷	÷	1	÷	1	1	÷	÷	÷		

Loctite Su

JB Weld Industrial JB Weld Industrial JB Kwik Weld

pack contains	code	list	price
2 x 28.5 g tubes	ADHJB8270		£7.50
2 x 142 g tubes	ADHJB8273	£24.99	£19.50
2 x 28.5 g tubes	ADHJB8276		£7.50



Gorilla Glue This incredibly strong polyurethane glue can bond pretty much anything including wood, stone, metal, ceramics, glass and foam. It is waterproof and temperature resistant, which means it is ideal for indoor and outdoor projects and repairs. For Gorilla Tape see page 272.

size	code	price
60 ml	ADHGPG0060	£6.71

Everbuild Thread Lock Handy-sized thread sealant for (surprise surprise) locking



threads on most nuts, bolts, and screws.						
Gap filling to 0.25 mm. Can be used on "as						
recieved" greasy nuts + bolts.						

code

code

ADH114

ADHETL10

Everbuild Thread Lock

Gorilla Glue



size

10 g

size

20 ml

Bostik All Purpose Sticks card, fabric, wood, metal, pottery, and most plastics. Not suitable for polystyrene, polypropylene, rayon or acetate.

Bostik All	Purpose	
Ha	andy size	



Everbuild High Viscosity Super Glue This higher viscosity super glue is easier to apply than standard super glue which can be a little runny. Suitable for use on most surfaces including non-porous surfaces like glass, metals, and PVCu. Sets in 10-30 seconds.

Everbuild High Viscosity Super Glue	code	price
50 g	ADHEVBHV50	£4.38

SPECIALIST COSTUME ADHESIVES



EGOOO+ & EGOOO+ Spray We first heard about this adhesive through the rather excellent Costume Networking group on Facebook [if you work in costume or wardrobe, we highly recommend you check it out - it's a mine of information!] and we quickly realised we needed to try it out for ourselves. Gary tested it out for us, and found it to be just the ticket - easy to use, didn't run on a vertical surface, adhered well to hard plastics, glass, metal, expanded polystyrene, fabrics (and remains flexible), can be put through a washer or dryer. The spray worked really well on wallpaper, and a hem! We can see this

could be extremely useful for model-makers too, as can be applied to painted surfaces without having nasty solvents dissolve the paints. How did we live without it? Odourless too. Popular for sticking gems onto costumes. We only stock this clear version as both a tube with nozzle applicator and a spray bottle.

E6000+	size	code	price
Tube	56.1 ml	ADHECL679	£8.50
Spray	236.5 ml	ADHECL023	£7.99

price

£3.56

price

£2.16